



## ACC-0808C DVR Card

### Key Features:

- H.264 Hardware Compressed DVR cards coming with PHILIPS Chipset.
- DVR Card Developed Under advanced motherboard-self-adapt technology which supports various chipset motherboards and display cards. This Technology reduces difficulty of selecting motherboard.
- CBR/HBR working mode is supported.
- D1 In Preview CIF In Recording.
- On HBR mode, code stream upper limit could be set, even the noise is bigger; the code stream could also be controlled.
- Dynamically real-time adjust brightness, contrast and other video parameter.
- 64 channels of encoding can supports in single PC, means you can use 4 pieces of ACC-0216C cards or 8 pieces of ACC-0808C DVR cards are supports in single PC.
- 64 Channels viewing simultaneously on single screen.
- Supports Automatic snapshot by customize time setting.

# ACC-0808C DVR Card



## Technical Specification:

### Video & Audio

#### ● Video

Video Compression : H.264.  
Playback resolution : PAL 704x576 (D1) , NTSC 640x480(D1)  
Video Input : 8 CH, BNC, 1Vp-p, 75Ω  
Sub code resolution : PAL 352 x 288(CIF), NTSC 352 x 240(CIF)  
Compression bit rate: 20K~4Mbps , selectable

#### ● Audio

Audio Compression : G.726  
Audio input : 8 ch audio input, RCA, 2Vp-p, 600Ω  
Audio Output : 1 ch RCA , 2Vp-p, 600Ω  
Sampling rate : 8KHZ  
Sampling size : 16 bit  
Audio track : single track

### Live Display & Recording

#### ● Live Display

Compression Format: D1

<b>System</b>	<b>: NTSC</b>	<b>PAL</b>
	704 X 480	704 X 576

#### ● Recording

Compression Format : CIF

<b>System</b>	<b>: NTSC</b>	<b>PAL</b>
<b>FPS@Resolution</b>	: 240FPS@352 x 240	200FPS@352 x 288

### Utilities & Alarm

#### ● Utility

Encoding : CBR / HBR.  
Video Setting : Brightness, Contrast, Hue, Saturation.  
Snapshot : To Store JPEG & BMP.

#### ● Alarm

Motion Detection : Zones: 192(16 x 12) detection zones  
Sensitivity: high, middle, common Trigger recording, preset position, PTZ movement, tour, alarm, upload to center.  
Video Loss : Trigger recording, PTZ movement, tour alarm, upload to center  
Alarm Input : 8 channel, constant open/closed supported  
Trigger recording, PTZ movement, tour, alarm, upload to center.  
Alarm Output : 4 channel, relay output 30VDC 1A.

### Dimension & Environment

#### ● Dimension

Product Dimensions : 151mm x 94mm (W x D)  
Gross Weight : 1 kg

#### ● Environment

Power Consumption : 0808C < 6W  
Temperature : 0°C ~ 55°C  
Humidity : 10% ~ 90%RH